

TOOL MODEL: MXTP-10

PRESSURE/TORQUE CONVERSION CHART

Standard Torque Chart

PDE001125 III		TOPOUT IN		DDE0011DE IX
PRESSURE IN PSI	FT.LBS.	TORQUE IN KGM	NM	PRESSURE IN BAR
1500	1831	253	2482	104
1600	1954	270	2649	110
1800	2201	304	2984	124
2000	2448	339	3319	138
2200	2696	373	3655	152
2400	2944	407	3991	165
2600	3192	441	4327	179
2800	3440	476	4663	193
3000	3688	510	4999	207
3200	3935	544	5334	220
3400	4182	578	5670	234
3600	4430	613	6005	248
3800	4677	647	6340	262
4000	4924	681	6675	276
4200	5171	715	7010	290
4400	5418	749	7344	303
4600	5664	783	7678	317
4800	5911	817	8013	331
5000	6157	852	8347	345
5200	6402	885	8679	358
5400	6647	919	9011	372
5600	6892	953	9342	386
5800	7136	987	9674	400
6000	7381	1021	10006	414
6200	7622	1054	10332	427
6400	7862	1087	10658	441
6600	8103	1121	10984	455
6800	8343	1154	11310	468
7000	8584	1187	11636	482
7200	8823	1220	11961	496
7400	9063	1253	12285	510
7600	9302	1286	12610	524
7800	9542	1320	12935	538
8000	9781	1353	13259	552
8200	10021	1386	13584	565
8400	10260	1419	13909	579
8600	10500	1452	14234	593
8800	10740	1485	14559	607
9000	10979	1518	14883	620
9200	11213	1551	15200	634
9400	11447	1583	15517	648
9600	11680	1615	15834	662
9800	11914	1648	16151	676
10000	12148	1680	16468	690

IMPORTANT SAFETY INSTRUCTIONS

WARNING: Your **HYTORC TORQUE MACHINE** is a power tool, and as with any power tool, certain safety precautions should be observed to avoid accidents or personal injury. The following tips will assist you.

- READ ALL INSTUCTIONS.
- KEEP WORK AREA CLEAN AND WELL LIT.
- CONSIDER WORK AREA ENVIRONMENT. Electrical Pumps should never be used in an atmosphere which can be considered potentially volatile. If there is any doubt, use an air pump. Also Note: metal to metal contact can cause sparks, precautions should be taken.
- AVOID PREMATURE TOOL STARTING. The Pump Remote Control is for the TOOL OPERATOR only.
- STAY CLEAR DURING OPERATION. In most cases, the tool will allow "hands free" operation. If the tool must be held or steadied during operation, use alternative means of securing the tool to the application
- GUARD AGAINS ELECTRIC SHOCK. Ensure the pump is properly grounded and the proper voltage is being used.
- STORE IDLE TOOLS. When not in use, tool sand accessories should be properly stored to avoid deterioration
- USE RIGHT TOOL. Don't force small tools or attachments to do the job of a larger tool. Don't use a tool for purposes not intended.
- **PROPER SAFETY ATTIRE.** When handling/operating hydraulic equipment use work gloves, hard hats, safety shoes and other applicable clothing.
- USE SAFETY GLASSES.
- **MOVING EQUIPMENT.** Do not use hydraulic hoses, uni-swivels, pump power or remote cords as means of moving the equipment.
- MAINTAIN TOOLS WITH CARE. For top performance, inspect tools, powerpack and accessories for visual damage frequently and always prior to use. Always follow instruction for proper tool and pump maintenance. Refer to the Operations Maintenance Section for further clarification
- STAY ALERT. Watch what you are doing. Use Common sense. Do not use power equipment under the influence of any mood altering substances.

PRIOR TO OPERATION

- Ensure that all hydraulic connections are securely connected and there is no leakage
- Verify that the Hydraulic hoses are not kinked or otherwise damaged.
- Ensure the square drive and its retainer are fully and securely engaged.
- Be certain that all connectors, elbows, fitting and swivels are not bent, loose or damaged.

PRIOR TO USE.

- Check sockets for size, quality and flaws. (Do not use if questionable)
- Cycle tool to ensure proper function.
- Locate a solid, secure reaction point.
- Be sure the reaction arm retaining clamp is fully engaged.
- Be sure the hydraulic hoses are free of the reaction point.
- Pressurize the system momentarily; if the tool tends to "ride up" or to "creep", stop and re-adjust the reaction arm to a more solid and secure position.

NOTE: Remain clear of the reaction arm during operation and never put body parts between reaction arm and reaction surfaces.

- ALWAYS USE QUALITY ACCESSORIES. Always use top quality impact sockets in good condition which are
 the correct size and fully engage the nut. Hidden flaws, however, remain a possibility which could cause
 breakage, so stay clear of sockets during operation
- DO NOR USE other equipment to enhance performance (Hammer on Socket/Tool)NOTE: Hytorc Pumps are
 designed to operate Hytorc Tools only. Damage may occur to the pump or the product that is being operated
 due to misuse.

SAVE THESE INSTRUCTIONS FOR FUTURE USE!